

# LINK ONE

## Technical specifications

Configuration	Panto Up	Panto Down
<b>Output</b>		
Power factor	> 0,98	
Efficiency [%]	> 94	
Maximum charging current [A]	500	850
<b>Communication</b>		
Charging mode	IEC 61851-1 IEC 61851-23 IEC 61851-24 ISO 15118 DIN 70121	
Protocol	OCPP 1.6-J OCPP 2.0.1	
<b>General</b>		
Housing	Steel with galvanised coating	
Protection rating	IP 54 IK 10	
Overall dimensions [ H x W x D ]	5000 x 1200 x 3045	
Weight [ Kg ]	~1500	~1500
Noise [ dBA ]	< 55	
Operating temperature range [ °C ]	- 25 - +55 > 40 possible output power limitation	
Operating altitude [m.a.s.l.]	≤ 2000	
Compliance with standards	CE LVD 2014/35/UE EMC 2014/30/UE RED 2014/53/UE	

# LINK ONE

## Equipment

### Configuration

Panto Up

Panto Down

#### Connectors

DC Connectors

Contact Dome

Inverted Pantograph

CCS Replacement  
plug (7m, 250A)



#### Housing

Colour

RAL 9016

RAL Colour  
(Other)

Option

Additional  
branding

Option

Anti-graffiti

Option

#### Interface

Emergency  
button



Charger status  
LED indication



#### Communication

Data transfer

Ethernet

**Catalog code**

**to order**